

NEW!

CURRENT PRODUCTS model:CSP906

MICPLUG



Microphone built-in XLR plug
Phantom power support
Simple setting
Compact
Omni direction

CSP906 is the microphone plug which included an electret condenser microphone in XLR plug. It can be directly connected to microphone preamplifier and a microphone panel connector and is most suitable for a purpose such as communication or simple sound collection. Moreover, it can set the low cut filter with an internal jumper, too and is effective when air conditioner noises are the problem. It works in 48V phantom power and can make use in various scenes such as a studio, broadcast, the live recording.

"Output"

It can extend the male connector of the general XLR3 pin with a cable.

"Low filter"

When it takes off one screw and removes an internal jumper plug, a low cut filter of 250Hz becomes effective. It has been set and can ship it.

"Phantom"

It can use it in a wide purpose in supporting to phantom power from 9V to 52V.

SPECIFICATIONS

- 🍏 **ELEMENT:** Electret Condenser
- 🍏 **OUTPUT CONNECTOR:** XLR3-M
- 🍏 **OUTPUT IMPEDANCE:** <600Ω
- 🍏 **DIRECTIVITY:** Omnidirectional
- 🍏 **POWER REQUIREMENT:** 9 to 52V phantom power
- 🍏 **CURRENT CONSUMPTION:** <3mA
- 🍏 **SENSITIVITY:** -46±3dB (0dB=1V/Pa at 1kHz)
- 🍏 **FREQ.RESPONSE:** 20Hz to 16kHz ±3dB
- 🍏 **SN:** >60dB (A-weighted)
- 🍏 **BASS ROLL OFF FILTER:** 250Hz, -10dB at 50Hz
- 🍏 **DIMENSIONS:** 19x111L, 60g

Mic plug	CSP906	¥4,800
accessory : none		

The specifications are subject to change without notice.
2-26-11 AKATSUTSUMI, SETAGAYA-KU, TOKYO, 156-0044 JAPAN